



Micro A12E Indicator



The Micro A12E Indicator acts as the heart of any weighing system, integrating seamlessly with platform scales, bench scales, and floor scales. Its high-precision A/D conversion technology delivers accurate and stable weight readings, while the bright red LED display ensures excellent visibility in any lighting environment.



Specifications

- Supports up to 4 load cells for stable, accurate weighing
- Bright 6-digit LED display with status indicators for units, alarms, and weighing state
- Dual power operation – mains or internal rechargeable battery
- RS-232 interface for connection to printers, computers, or control systems
- Selectable digital filtering and stabilization time to reduce vibration interference
- High-precision A/D conversion for fast, stable readings
- Load cell excitation: DC 5 V, \leq 150 mA
- Accuracy: Class III
- Verification Counts: 3,000 | Maximum External Counts: 30,000
- Operating temperature: 0 °C to 40 °C
- Ingress Protection: IP54 (dust and splash protected)
- Enhanced EMC design for reduced interference from external sources



Border Scales cc
Physical Address:
Cnr Courtenay & Keats Street,
Cambridge, East London, 5247
Contact us
Tel No.: 043 - 726 2801

Our Services

Border Scales is accredited by SANAS and NRCS to perform Legal Metrology Verification of scales used in trade within our scope of 3kg to 3000kg.

Our trained and skilled technicians will service, calibrate and repair all equipment we sell. We offer in-house training on all new equipment installations.

